

PERFORMANCE LEVELS, WARRANTY



Copper

ROOF WALKWAY, ROOF STEP LADDERS, SNOW FENCES

Copper ROOF WALKWAY

Unique identification code of the product-type and the declared performance

The roof walkway made of copper is tested according to EN 516:2006 type B standard with 1,5 kN static test load based on a theoretical working load of one user (100 kg) with safety factor. The test simulates one person walking along the roof walk way at normal conditions. Design and dimensions of the product meet the requirements of EN-standard.

Name	Product code	Installation guide
Roof walkway 2.97 m	30033KI	KS3CU
Roof walkway 2.25 m	30203KI	
Roof walkway 1.21 m	30014KI	
Upper supporter	30064KI	
Seam fastener set	35643KI	

Intended use of building product

Roof access (building products) permanently fixed to the load-bearing construction of pitched roofs, to stand or to walk on during inspection, maintenance and repair of facilities on the roof.

Copper ROOF STEP LADDERS

Unique identification code of the product-type and the declared performance

The roof step ladder made of copper is tested according to EN 12951:2004 type B standard with 1,5 kN static test load based on a theoretical working load of one user (100 kg) with safety factor. The test simulates one person walking along the roof step ladder at normal conditions. Design and dimensions of the product meet the requirements of EN-standard.

Name	Product code	Installation guide
Roof step ladder 1.2 m	22013KI	KR2CU
Roof step ladder 2.4 m	22033KI	
Seam fastener set	22153KI	

Intended use of building product

Permanently fixed ladders made of metal which are permanently installed on the load-bearing construction of pitched roofs and which may be stepped or walked on for purposes of inspection, maintenance and repair of equipment installed above the roof surface.

Copper SNOW FENCES

Unique identification code of the product-type and the declared performance

The snow fence made of copper is tested according to SS 8313667 standard with 5 kN/m static test load. Design and dimensions of the product meet the requirements of SS-standard.

Name	Product code	Installation guide
Round tube 2.5 m	31013KI	LE2CU
Seam fastener set	35643KI	

Intended use of building product

Horizontal barrier permanently fixed to the construction of pitched roofs, prevent accumulated snow from falling and moving, protect the coating of the roof and persons, constructions and equipment near the building.

Name of Manufacturer

Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila
+358 3 872 100, www.orima.fi, myynti@orima.fi

The performance of the products identified in this document is conformity with the declared performance. These performance levels are issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Orimattila, 1.10.2018

Mikko Ahonen, CEO