

DECLARATION OF PERFORMANCE



ROOF FENCES

Unique identification code of the product-type:

Orima® Roof fences

| Name | Product code | Installation guide |
|-------------------------|--------------|---|
| Oval tube 3,0 m | 31010 | SYP, SYPL, SYV, SYVL, SYO, SYOL, SYT, SYTL, SYS, SYSL, SYR, SYRL, SYN, SYNL |
| Lower supporter profile | 30530 | SYT, SYTL, SYS, SYL |
| Vertical support 0,50 m | 33490 | SYT, SYTL, SYV, SYVL, SYR, SYRL |
| Diagonal support 0,80 m | 33480 | SYT, SYTL, SYV, SYVL, SYR, SYRL |
| Lower supporter | 30070 | SYO, SYOL, SYV, SYVL |
| Diagonal support 1,10 m | 33440 | SYO, SYOL, SYS, SYSL, SYN, SYNL |
| Vertical support 0,95 m | 33460 | SYO, SYOL, SYS, SYSL, SYN, SYNL |
| Console | 33470 | SYP, SYPL |
| D-loop | 20530 | SYP, SYPL |
| Seam fastener set | 35640 | SYN, SYNL, SYR, SYRL |
| Seam fastener | 22170 | SYN, SYNL, SYR, SYRL |

Intended use of building product

Horizontal barrier permanently fixed to the construction of pitched roofs, prevents a person from falling off the roof.

Name of Manufacturer

Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila
+358 3 872 100, www.orima.fi, myynti@orima.fi

Product testing Roof fences are tested according to GOST R 53254-2009. There is not a harmonised standard for roof fences and therefore cannot be CE marked.

Declared performance

| Essential characteristics | Performance | Standard |
|---------------------------|--|-------------------|
| Mechanical strength | Static strength: Horizontally load 0,54 kN according to 6.2.15 | GOST R 53254-2009 |
| Dimensions | according to the table D.1 | |

The performance of the product identified in this document is conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Orimattila, 15.6.2018

Mikko Ahonen, CEO